

**Security  
User Guide  
8.7.2025.07**

# Copyright

---

© 2012-2020 Qlik Analytics (ISR) Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or for any purpose without the express permission of Qlik Analytics (ISR) Ltd.

Qlik Analytics (ISR) Ltd. makes no warranties or representations with respect to the content hereof and assumes no responsibility for errors in this document. Qlik Analytics (ISR) Ltd. shall not be liable for special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits which may result from the use of these materials. The information contained in this document is subject to change without notice.

# Trademarks

---

Gold Client and the Gold Client logo are registered trademarks of Qlik Analytics (ISR) Ltd.

SAP, SAP NetWeaver, ABAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world.

All other product and company names herein may be trademarks of their respective owners.

# Table of Contents

Introduction .....	4
Gold Client Security Object .....	5
Authorization Object ZGCSGCSGCS.....	5
Authorization Object Activities .....	6
Sample Roles.....	8
Basis Role.....	8
<i>Basis Role</i> – Gold Client Screen Example.....	10
Super User Role.....	11
<i>Super User Role</i> – Gold Client Screen Example.....	13
End User Role.....	14
<i>End User Role</i> – Gold Client Screen Example.....	16
Gold Client Security Programs and Application Settings.....	17
Activating Security - /HTG/OP.....	17
Inactivating Security - /HTG/VAN.....	17
Authorization Group ZHTGGOLD.....	18
Locking Down a Client.....	19
Additional SAP Security Required for Gold Client .....	21
S_TCODE.....	21
S_TABU_DIS.....	21
S_DATASET .....	21
RFC Destinations in Gold Client .....	22
Import Options - RFC Users.....	22
S_TCODE .....	23
S_TABU_DIS .....	23
S_DATASET.....	23
ZGCSGCSGCS.....	24
Subset Sync - RFC Users.....	24
S_TCODE .....	25
S_TABU_DIS .....	25
S_DATASET.....	25
ZGCSGCSGCS.....	26
Appendix .....	26
Client Construct .....	26
Repository Replicator.....	28
Data Echo.....	29
Data Snap.....	29
Intelligent Slice.....	30
Scenario Segment .....	30
Export Control .....	31
Import Control .....	32
Transformation Rules.....	33
Transformation Default Rules Security/Use.....	34
Data Discard .....	35
Configuration .....	36
Post Process .....	38
Data Wave.....	39
Support Information.....	41

# Introduction

---

This document serves as a guide for enabling and configuring the security authorization for use with Qlik Gold Client. This guide will explain the Gold Client authorization object and other authorizations required to execute different parts of the software.

Additional security is built into the tool so when Gold Client is installed in production the import functionality and selective deletion functionality is disabled.

# Gold Client Security Object


Gold Client delivers its own authorization object ZGCSGCSGCS. Each button on the main Gold Client screen can be activated or deactivated with this authorization object. Along with this object there are additional authorizations needed to enable the Gold Client user to use the software.

## Authorization Object ZGCSGCSGCS

The authorization object ZGCSGCSGCS when added to a role gives the ability to enable or disable certain functions within Gold Client. The authorization is controlled by enabling or disabling each button within the various Gold Client screens. Qlik Gold Client does not deliver pre-built roles for authorization object ZGCSGCSGCS in order to allow for customers to create their own roles based on their business processes.

Below is the main screen of Gold Client Solutions (Fig. 1.1). Each button displayed on this screen and all subsequent screens are controlled by the various activities within authorization object ZGCSGCSGCS.

Figure 1.1



## Authorization Object Activities

---

There are a large number of activities assigned to the Gold Client authorization object ZGCSGCSGCS (Figs. 1.2 through 1.4). Qlik Gold Client groups security activities in numeric order based on the functionality they serve. Screenshots below show the activities assigned to authorization object ZGCSGCSGCS.

Figure 1.2

01	Client Construct: Client Exporter: Transport Request
02	Client Construct: Client Exporter: Direct Export
03	Client Construct: Client Importer: Transport Request
04	Client Construct: Client Importer: Direct Input
05	Repository Replicator: Object Alignment
06	Repository Replicator: Create Transport of Object Difference
07	Repository Replicator: Recall Previous Run
08	Repository Replicator: Additional Objects
09	Repository Replicator: System Build Plus
10	Data Echo: Data Snap
11	Data Echo: Data Snap: Schedule Job
12	Data Echo: Data Snap: Show Count
13	Data Echo: Data Snap: Save As Scenario
14	Data Echo: Data Snap: Import Trigger
15	Data Echo: Data Snap: Subset Sync
16	Data Echo: Data Snap: Data Transform
17	Data Echo: Data Snap: Data Type Manager
20	Data Echo: Intelligent Slice
30	Data Echo: Scenario Segment
31	Data Echo: Scenario Segment: Scenario Manager
32	Data Echo: Scenario Segment: Data Type Manager
40	Data Echo: Export Control
41	Data Echo: Export Control: Change Mode
42	Data Echo: Export Control: Create Export ID
43	Data Echo: Export Control: Delete Export ID
44	Data Echo: Export Control: Show All Exports
45	Data Echo: Export Control: Execute in Foreground
46	Data Echo: Export Control: Schedule Job
47	Data Echo: Export Control: Import Trigger
48	Data Echo: Export Control: Subset Sync
49	Data Echo: Export Control: Data Transform
50	Data Echo: Import Control
51	Data Echo: Import Control: Details
52	Data Echo: Import Control: Report

Figure 1.3

53	Data Echo: Import Control: Execute in Foreground
54	Data Echo: Import Control: Schedule Job
55	Data Echo: Import Control: Delete Files
56	Data Echo: Import Control: Generate & Activate IM
57	Data Echo: Import Control: Sizing Report: Export File
60	Data Transform: Transformation Setup
61	Data Transform: Change Rules
62	Data Transform: Maintain Disallowed Fields
63	Data Transform: Maintain List Values
64	Data Transform: Maintain Default Rules
65	Data Transform: Client Construct
66	Data Transform: Export TRA Details
67	Data Transform: Display Transformed Fields
70	Data Discard: Delete Data
71	Data Discard: Details
72	Data Discard: Report
73	Data Discard: Execute in Foreground
74	Data Discard: Schedule Job
75	Data Discard: Delete Files
80	Configuration: Display Only
81	Configuration: Administration
82	Configuration: Installation/Setup
83	Configuration: Framework: Display Only
84	Configuration: Framework: Client Construct: Change Access
85	Configuration: Framework: Data Echo: Change Access
86	Configuration: Utilities
87	Configuration: Advanced Utilities
88	Configuration: Utilities: Finance
89	Configuration: Utilities: Conversions
90	Scenario Manager: Manage All Users
91	Configuration: Utilities: HR
100	Data Wave: Cockpit
101	Data Wave: Prepare Client
102	Data Wave: Copy Config and Users
103	Not Applicable
105	Data Wave: Import Client Data
106	Data Wave: Reset Client Data

Figure 1.4

107	Data Wave: Delete Data
110	Data Wave: Client Construct Import
111	Data Wave: Data Echo import
112	Data Wave: Post Processing
115	Data Wave: Identify and Export
116	Data Wave: Data Discovery
117	Data Wave: Client Construct Export
118	Data Wave: Data Echo Export
120	Data Wave: Export Status
125	Data Wave: Import Status
130	Data Wave: Configuration

## Sample Roles

---

The following are three sample roles for using Gold Client. They are examples of how the authorizations can be configured for different users and can easily be adjusted for different activities depending on the user's role. During the installation and training of the Gold Client software, roles and responsibilities will be discussed.

### *Basis Role*

---

A sample Basis role would enable the Basis resource to execute all parts of the Gold Client tool. In most cases, the Basis team will be responsible for moving data from a source client to the target client during a client build for your organization. The following screenshots (Figs. 1.5 – 1.7) demonstrate which activities are recommended for the Basis resources in order to use Gold Client fully.

Figure 1.5

Fixed Val.	Upper limit	Short Descript.
<input checked="" type="checkbox"/>	01	Client Construct: Client Exporter: Transport Request
<input checked="" type="checkbox"/>	02	Client Construct: Client Exporter: Direct Export
<input checked="" type="checkbox"/>	03	Client Construct: Client Importer: Transport Request
<input checked="" type="checkbox"/>	04	Client Construct: Client Importer: Direct Input
<input checked="" type="checkbox"/>	05	Repository Replicator: Object Alignment
<input checked="" type="checkbox"/>	06	Repository Replicator: Create Transport of Object Difference
<input checked="" type="checkbox"/>	07	Repository Replicator: Recall Previous Run
<input checked="" type="checkbox"/>	08	Repository Replicator: Additional Objects
<input checked="" type="checkbox"/>	09	Repository Replicator: System Build Plus
<input checked="" type="checkbox"/>	10	Data Echo: Data Snap
<input checked="" type="checkbox"/>	11	Data Echo: Data Snap: Schedule Job
<input checked="" type="checkbox"/>	12	Data Echo: Data Snap: Show Count
<input checked="" type="checkbox"/>	13	Data Echo: Data Snap: Save As Scenario
<input checked="" type="checkbox"/>	14	Data Echo: Data Snap: Import Trigger
<input checked="" type="checkbox"/>	15	Data Echo: Data Snap: Subset Sync
<input checked="" type="checkbox"/>	16	Data Echo: Data Snap: Data Transform
<input checked="" type="checkbox"/>	17	Data Echo: Data Snap: Data Type Manager
<input checked="" type="checkbox"/>	20	Data Echo: Intelligent Slice
<input checked="" type="checkbox"/>	30	Data Echo: Scenario Segment
<input checked="" type="checkbox"/>	31	Data Echo: Scenario Segment: Scenario Manager
<input checked="" type="checkbox"/>	32	Data Echo: Scenario Segment: Data Type Manager
<input checked="" type="checkbox"/>	40	Data Echo: Export Control
<input checked="" type="checkbox"/>	41	Data Echo: Export Control: Change Mode
<input checked="" type="checkbox"/>	42	Data Echo: Export Control: Create Export ID
<input checked="" type="checkbox"/>	43	Data Echo: Export Control: Delete Export ID
<input checked="" type="checkbox"/>	44	Data Echo: Export Control: Show All Exports
<input checked="" type="checkbox"/>	45	Data Echo: Export Control: Execute in Foreground
<input checked="" type="checkbox"/>	46	Data Echo: Export Control: Schedule Job
<input checked="" type="checkbox"/>	47	Data Echo: Export Control: Import Trigger
<input checked="" type="checkbox"/>	48	Data Echo: Export Control: Subset Sync
<input checked="" type="checkbox"/>	49	Data Echo: Export Control: Data Transform
<input checked="" type="checkbox"/>	50	Data Echo: Import Control

Figure 1.6

Fixed Val.	Upper limit	Short Descript.
✓ 51		Data Echo: Import Control: Details
✓ 52		Data Echo: Import Control: Report
✓ 53		Data Echo: Import Control: Execute in Foreground
✓ 54		Data Echo: Import Control: Schedule Job
✓ 55		Data Echo: Import Control: Delete Files
✓ 56		Data Echo: Import Control: Generate & Activate IM
✓ 57		Data Echo: Import Control: Sizing Report: Export File
✓ 60		Data Transform: Transformation Setup
✓ 61		Data Transform: Change Rules
✓ 62		Data Transform: Maintain Disallowed Fields
✓ 63		Data Transform: Maintain List Values
✓ 64		Data Transform: Maintain Default Rules
✓ 65		Data Transform: Client Construct
✓ 66		Data Transform: Export TRA Details
✓ 67		Data Transform: Display Transformed Fields
✓ 70		Data Discard: Delete Data
✓ 71		Data Discard: Details
✓ 72		Data Discard: Report
✓ 73		Data Discard: Execute in Foreground
✓ 74		Data Discard: Schedule Job
✓ 75		Data Discard: Delete Files
✓ 80		Configuration: Display Only
✓ 81		Configuration: Administration
✓ 82		Configuration: Installation/Setup
✓ 83		Configuration: Framework: Display Only
✓ 84		Configuration: Framework: Client Construct: Change Access
✓ 85		Configuration: Framework: Data Echo: Change Access
✓ 86		Configuration: Utilities
✓ 87		Configuration: Advanced Utilities
✓ 88		Configuration: Utilities: Finance
✓ 89		Configuration: Utilities: Conversions
✓ 90		Scenario Manager: Manage All Users

Figure 1.7

✓ 91		Configuration: Utilities: HR
✓ 100		Data Wave: Cockpit
✓ 101		Data Wave: Prepare Client
✓ 102		Data Wave: Copy Config and Users
✓ 103		Not Applicable
✓ 105		Data Wave: Import Client Data
✓ 106		Data Wave: Reset Client Data
✓ 107		Data Wave: Delete Data
✓ 110		Data Wave: Client Construct Import
✓ 111		Data Wave: Data Echo import
✓ 112		Data Wave: Post Processing
✓ 115		Data Wave: Identify and Export
✓ 116		Data Wave: Data Discovery
✓ 117		Data Wave: Client Construct Export
✓ 118		Data Wave: Data Echo Export
✓ 120		Data Wave: Export Status
✓ 125		Data Wave: Import Status
✓ 130		Data Wave: Configuration


## Basis Role – Gold Client Screen Example

The sample Basis role will display as follows in your SAP Production System (Fig. 1.8) and other non-Production Systems (Fig. 1.9)

Figure 1.8



Figure 1.9



## Super User Role

A sample Super User role would enable the same activities as the Basis role but excludes those functions that are typically specific to just Basis Resources (Client Construct and Repository Replicator). The following screenshots (Figs. 1.10 – 1.12) demonstrate which activities are recommended for the Super User Role in order to use Gold Client.

Figure 1.10

	Fixed Val.	Upper limit	Short Descript.
<input type="checkbox"/>	01		Client Construct: Client Exporter: Transport Request
<input type="checkbox"/>	02		Client Construct: Client Exporter: Direct Export
<input type="checkbox"/>	03		Client Construct: Client Importer: Transport Request
<input type="checkbox"/>	04		Client Construct: Client Importer: Direct Input
<input type="checkbox"/>	05		Repository Replicator: Object Alignment
<input type="checkbox"/>	06		Repository Replicator: Create Transport of Object Difference
<input type="checkbox"/>	07		Repository Replicator: Recall Previous Run
<input type="checkbox"/>	08		Repository Replicator: Additional Objects
<input type="checkbox"/>	09		Repository Replicator: System Build Plus
<input checked="" type="checkbox"/>	10		Data Echo: Data Snap
<input checked="" type="checkbox"/>	11		Data Echo: Data Snap: Schedule Job
<input checked="" type="checkbox"/>	12		Data Echo: Data Snap: Show Count
<input checked="" type="checkbox"/>	13		Data Echo: Data Snap: Save As Scenario
<input checked="" type="checkbox"/>	14		Data Echo: Data Snap: Import Trigger
<input checked="" type="checkbox"/>	15		Data Echo: Data Snap: Subset Sync
<input checked="" type="checkbox"/>	16		Data Echo: Data Snap: Data Transform
<input checked="" type="checkbox"/>	17		Data Echo: Data Snap: Data Type Manager
<input checked="" type="checkbox"/>	20		Data Echo: Intelligent Slice
<input checked="" type="checkbox"/>	30		Data Echo: Scenario Segment
<input checked="" type="checkbox"/>	31		Data Echo: Scenario Segment: Scenario Manager
<input checked="" type="checkbox"/>	32		Data Echo: Scenario Segment: Data Type Manager
<input checked="" type="checkbox"/>	40		Data Echo: Export Control
<input checked="" type="checkbox"/>	41		Data Echo: Export Control: Change Mode
<input checked="" type="checkbox"/>	42		Data Echo: Export Control: Create Export ID
<input checked="" type="checkbox"/>	43		Data Echo: Export Control: Delete Export ID
<input checked="" type="checkbox"/>	44		Data Echo: Export Control: Show All Exports
<input checked="" type="checkbox"/>	45		Data Echo: Export Control: Execute in Foreground
<input checked="" type="checkbox"/>	46		Data Echo: Export Control: Schedule Job
<input checked="" type="checkbox"/>	47		Data Echo: Export Control: Import Trigger
<input checked="" type="checkbox"/>	48		Data Echo: Export Control: Subset Sync
<input checked="" type="checkbox"/>	49		Data Echo: Export Control: Data Transform
<input checked="" type="checkbox"/>	50		Data Echo: Import Control

Figure 1.11

	Fixed Val.	Upper limit	Short Descript.
<input checked="" type="checkbox"/>	51		Data Echo: Import Control: Details
<input checked="" type="checkbox"/>	52		Data Echo: Import Control: Report
<input checked="" type="checkbox"/>	53		Data Echo: Import Control: Execute in Foreground
<input checked="" type="checkbox"/>	54		Data Echo: Import Control: Schedule Job
<input checked="" type="checkbox"/>	55		Data Echo: Import Control: Delete Files
<input checked="" type="checkbox"/>	56		Data Echo: Import Control: Generate & Activate IM
<input checked="" type="checkbox"/>	57		Data Echo: Import Control: Sizing Report: Export File
<input checked="" type="checkbox"/>	60		Data Transform: Transformation Setup
<input checked="" type="checkbox"/>	61		Data Transform: Change Rules
<input checked="" type="checkbox"/>	62		Data Transform: Maintain Disallowed Fields
<input checked="" type="checkbox"/>	63		Data Transform: Maintain List Values
<input checked="" type="checkbox"/>	64		Data Transform: Maintain Default Rules
<input checked="" type="checkbox"/>	65		Data Transform: Client Construct
<input checked="" type="checkbox"/>	66		Data Transform: Export TRA Details
<input checked="" type="checkbox"/>	67		Data Transform: Display Transformed Fields
<input checked="" type="checkbox"/>	70		Data Discard: Delete Data
<input checked="" type="checkbox"/>	71		Data Discard: Details
<input checked="" type="checkbox"/>	72		Data Discard: Report
<input checked="" type="checkbox"/>	73		Data Discard: Execute in Foreground
<input checked="" type="checkbox"/>	74		Data Discard: Schedule Job
<input checked="" type="checkbox"/>	75		Data Discard: Delete Files
<input checked="" type="checkbox"/>	80		Configuration: Display Only
<input checked="" type="checkbox"/>	81		Configuration: Administration
<input checked="" type="checkbox"/>	82		Configuration: Installation/Setup
<input checked="" type="checkbox"/>	83		Configuration: Framework: Display Only
<input checked="" type="checkbox"/>	84		Configuration: Framework: Client Construct: Change Access
<input checked="" type="checkbox"/>	85		Configuration: Framework: Data Echo: Change Access
<input checked="" type="checkbox"/>	86		Configuration: Utilities
<input checked="" type="checkbox"/>	87		Configuration: Advanced Utilities
<input checked="" type="checkbox"/>	88		Configuration: Utilities: Finance
<input checked="" type="checkbox"/>	89		Configuration: Utilities: Conversions
<input checked="" type="checkbox"/>	90		Scenario Manager: Manage All Users

Figure 1.12

<input checked="" type="checkbox"/>	91		Configuration: Utilities: HR
<input checked="" type="checkbox"/>	100		Data Wave: Cockpit
<input checked="" type="checkbox"/>	101		Data Wave: Prepare Client
<input checked="" type="checkbox"/>	102		Data Wave: Copy Config and Users
<input checked="" type="checkbox"/>	103		Not Applicable
<input checked="" type="checkbox"/>	105		Data Wave: Import Client Data
<input checked="" type="checkbox"/>	106		Data Wave: Reset Client Data
<input checked="" type="checkbox"/>	107		Data Wave: Delete Data
<input checked="" type="checkbox"/>	110		Data Wave: Client Construct Import
<input checked="" type="checkbox"/>	111		Data Wave: Data Echo import
<input checked="" type="checkbox"/>	112		Data Wave: Post Processing
<input checked="" type="checkbox"/>	115		Data Wave: Identify and Export
<input checked="" type="checkbox"/>	116		Data Wave: Data Discovery
<input checked="" type="checkbox"/>	117		Data Wave: Client Construct Export
<input checked="" type="checkbox"/>	118		Data Wave: Data Echo Export
<input checked="" type="checkbox"/>	120		Data Wave: Export Status
<input checked="" type="checkbox"/>	125		Data Wave: Import Status
<input checked="" type="checkbox"/>	130		Data Wave: Configuration

## Super User Role – Gold Client Screen Example

The sample Super User Role will display as follows in your SAP Production System (Fig. 1.13) and non-Production Systems (Fig. 1.14). Make note that any activities not assigned will be greyed out within the Gold Client screens and users will not be able to utilize those buttons/activities for which they are not assigned.

Figure 1.13





Figure 1.14



## End User Role

The sample End User Role enables authorization to define the data criteria for exports and to build an Export ID but does not allow for exporting or importing of data. This example also enables the use of Utilities and the ability to display the Framework for Client Construct and Data Echo, but not the ability to change the Framework. The following screenshots (Figs. 1.15 – 1.17) demonstrate which activities are recommended for the Super User Role in order to use Gold Client.

Figure 1.15

	Fixed Val.	Upper limit	Short Descript.
<input type="checkbox"/>	01		Client Construct: Client Exporter: Transport Request
<input type="checkbox"/>	02		Client Construct: Client Exporter: Direct Export
<input type="checkbox"/>	03		Client Construct: Client Importer: Transport Request
<input type="checkbox"/>	04		Client Construct: Client Importer: Direct Input
<input type="checkbox"/>	05		Repository Replicator: Object Alignment
<input type="checkbox"/>	06		Repository Replicator: Create Transport of Object Difference
<input type="checkbox"/>	07		Repository Replicator: Recall Previous Run
<input type="checkbox"/>	08		Repository Replicator: Additional Objects
<input type="checkbox"/>	09		Repository Replicator: System Build Plus
<input checked="" type="checkbox"/>	10		Data Echo: Data Snap
<input type="checkbox"/>	11		Data Echo: Data Snap: Schedule Job
<input checked="" type="checkbox"/>	12		Data Echo: Data Snap: Show Count
<input checked="" type="checkbox"/>	13		Data Echo: Data Snap: Save As Scenario
<input type="checkbox"/>	14		Data Echo: Data Snap: Import Trigger
<input type="checkbox"/>	15		Data Echo: Data Snap: Subset Sync
<input type="checkbox"/>	16		Data Echo: Data Snap: Data Transform
<input type="checkbox"/>	17		Data Echo: Data Snap: Data Type Manager
<input checked="" type="checkbox"/>	20		Data Echo: Intelligent Slice
<input checked="" type="checkbox"/>	30		Data Echo: Scenario Segment
<input checked="" type="checkbox"/>	31		Data Echo: Scenario Segment: Scenario Manager
<input type="checkbox"/>	32		Data Echo: Scenario Segment: Data Type Manager
<input checked="" type="checkbox"/>	40		Data Echo: Export Control
<input checked="" type="checkbox"/>	41		Data Echo: Export Control: Change Mode
<input checked="" type="checkbox"/>	42		Data Echo: Export Control: Create Export ID
<input checked="" type="checkbox"/>	43		Data Echo: Export Control: Delete Export ID
<input type="checkbox"/>	44		Data Echo: Export Control: Show All Exports
<input type="checkbox"/>	45		Data Echo: Export Control: Execute in Foreground
<input type="checkbox"/>	46		Data Echo: Export Control: Schedule Job
<input type="checkbox"/>	47		Data Echo: Export Control: Import Trigger
<input type="checkbox"/>	48		Data Echo: Export Control: Subset Sync
<input type="checkbox"/>	49		Data Echo: Export Control: Data Transform
<input type="checkbox"/>	50		Data Echo: Import Control

Figure 1.16

Fixed Val.	Upper limit	Short Descript.
<input type="checkbox"/>		51 Data Echo: Import Control: Details
<input type="checkbox"/>		52 Data Echo: Import Control: Report
<input type="checkbox"/>		53 Data Echo: Import Control: Execute in Foreground
<input type="checkbox"/>		54 Data Echo: Import Control: Schedule Job
<input type="checkbox"/>		55 Data Echo: Import Control: Delete Files
<input type="checkbox"/>		56 Data Echo: Import Control: Generate & Activate IM
<input type="checkbox"/>		57 Data Echo: Import Control: Sizing Report: Export File
<input type="checkbox"/>		60 Data Transform: Transformation Setup
<input type="checkbox"/>		61 Data Transform: Change Rules
<input type="checkbox"/>		62 Data Transform: Maintain Disallowed Fields
<input type="checkbox"/>		63 Data Transform: Maintain List Values
<input type="checkbox"/>		64 Data Transform: Maintain Default Rules
<input type="checkbox"/>		65 Data Transform: Client Construct
<input type="checkbox"/>		66 Data Transform: Export TRA Details
<input type="checkbox"/>		67 Data Transform: Display Transformed Fields
<input type="checkbox"/>		70 Data Discard: Delete Data
<input type="checkbox"/>		71 Data Discard: Details
<input type="checkbox"/>		72 Data Discard: Report
<input type="checkbox"/>		73 Data Discard: Execute in Foreground
<input type="checkbox"/>		74 Data Discard: Schedule Job
<input type="checkbox"/>		75 Data Discard: Delete Files
<input checked="" type="checkbox"/>		80 Configuration: Display Only
<input type="checkbox"/>		81 Configuration: Administration
<input type="checkbox"/>		82 Configuration: Installation/Setup
<input checked="" type="checkbox"/>		83 Configuration: Framework: Display Only
<input type="checkbox"/>		84 Configuration: Framework: Client Construct: Change Access
<input type="checkbox"/>		85 Configuration: Framework: Data Echo: Change Access
<input checked="" type="checkbox"/>		86 Configuration: Utilities
<input type="checkbox"/>		87 Configuration: Advanced Utilities
<input type="checkbox"/>		88 Configuration: Utilities: Finance
<input type="checkbox"/>		89 Configuration: Utilities: Conversions
<input type="checkbox"/>		90 Scenario Manager: Manage All Users

Figure 1.17

<input type="checkbox"/>		91 Configuration: Utilities: HR
<input type="checkbox"/>		100 Data Wave: Cockpit
<input type="checkbox"/>		101 Data Wave: Prepare Client
<input type="checkbox"/>		102 Data Wave: Copy Config and Users
<input type="checkbox"/>		103 Not Applicable
<input type="checkbox"/>		105 Data Wave: Import Client Data
<input type="checkbox"/>		106 Data Wave: Reset Client Data
<input type="checkbox"/>		107 Data Wave: Delete Data
<input type="checkbox"/>		110 Data Wave: Client Construct Import
<input type="checkbox"/>		111 Data Wave: Data Echo import
<input type="checkbox"/>		112 Data Wave: Post Processing
<input type="checkbox"/>		115 Data Wave: Identify and Export
<input type="checkbox"/>		116 Data Wave: Data Discovery
<input type="checkbox"/>		117 Data Wave: Client Construct Export
<input type="checkbox"/>		118 Data Wave: Data Echo Export
<input type="checkbox"/>		120 Data Wave: Export Status
<input type="checkbox"/>		125 Data Wave: Import Status
<input type="checkbox"/>		130 Data Wave: Configuration

## End User Role – Gold Client Screen Example

The sample End User Role will display as follows in your SAP Production System (Fig. 1.18) and non-Production Systems (Fig.1.19). Make note that any activities not assigned will be greyed out within the Gold Client screens and users will not be able to utilize those buttons/activities for which they are not assigned.

Figure 1.18





Figure 1.19



# Gold Client Security Programs and Application Settings

Gold Client is installed with the authorization object disabled. There are two programs that are delivered with Gold Client in order to turn security on and off in your SAP environment. Program /HTG/OP turns security on and program /HTG/VAN turns security off within the client in which the programs are executed. In order to execute these programs in your SAP environment, security will need to be assigned to the resource who is executing the programs (documentation below regarding the additional security object required for these program executions).

**Note: Programs /HTG/OP and /HTG/VAN process immediately, however they do not display output, nor a status message and do not give any indication that they have been completed. (updated as of Gold Client 8.7.2025.02 – see below)**

## Activating Security - /HTG/OP


To enable the Gold Client security the following program needs to be executed with transaction SE38: **/HTG/OP**

## Inactivating Security - /HTG/VAN

If there is a requirement to disable Gold Client Security in a client, the following program needs to be executed with transaction SE38: **/HTG/VAN**

**As of Gold Client 8.7.2025.02, these programs now show a message when executed:**

### **/HTG/OP**



### **/HTG/VAN**



The Configuration -> Administration -> Installation/Setup -> Setup Confirmation screen now shows the Gold Client Authorization Object status.

## /HTG/OP

Configuration checklist		
Configuration Name	Stat...	Message
Write to File	○○■	CONFIG_TEST file was succesfully writen
Read From File	○○■	Successfully read the file
Transaction /HTG/ZGOLD	○○■	Authorization check passed
Authorization Object	○○■	Gold Client security is enabled
Client Construct Config	○○■	Client Construct Config exists in the current system
Data Echo Config	○○■	Data Echo Config exists in the current system

## /HTG/VAN

Configuration checklist		
Configuration Name	Stat...	Message
Write to File	○○■	CONFIG_TEST file was succesfully writen
Read From File	○○■	Successfully read the file
Transaction /HTG/ZGOLD	○○■	Authorization check passed
Authorization Object	○○▲	Gold Client security is disabled
Client Construct Config	○○■	Client Construct Config exists in the current system
Data Echo Config	○○■	Data Echo Config exists in the current system

## Authorization Group ZHTGGOLD

Programs /HTG/OP and /HTG/VAN are assigned to authorization group ZHTGGOLD (Fig. 1.20).

In order to successfully execute these programs additional security authorization is required (only for those users who will enable/disable Gold Client Security):

OBJECT = S\_PROGRAM, P\_ACTION = SUBMIT, P\_GROUP = ZHTGGOLD

Figure 1.20

The screenshot shows the configuration for the authorization object S\_PROGRAM. It is set to 'Manually' and 'ABAP: Program Flow Checks'. The configuration is expanded to show the following details:

Manually	ABAP: Program Flow Checks	S_PROGRAM
Manually	ABAP: Program Flow Checks	T-EN98002100
User action ABAP/4 program	SUBMIT	P_ACTION
Authorization group ABAP/4 pro	ZHTGGOLD	P_GROUP


## Locking Down a Client

There is a feature within the Gold Client that locks down a client to prevent imports or deletions from occurring via the tool. This feature can be useful on those occasions when a client needs to be in a “frozen” state for a temporary period or to prevent users from using the tool in a client that was not created with Best Practice recommendations.

The IMPORT\_DISABLE application setting is client-dependent so activating it will affect only the client where this change is deployed.


This feature is located within the Configuration menu by selecting the executable named “Application Settings (mconfig)”. This executable can be found underneath the Administration folder within the Configuration menu (Fig. 1.21).

Figure 1.21



To deploy this change, the application setting `IMPORT_DISABLE` must be selected as 'Active' and then saved using the 'Save Configuration' button within Gold Client (Fig. 1.22).

Figure 1.22



After this change is deployed, if a user attempts to run the import or delete programs within Gold Client, the following message appears (Fig. 1.23), and the user will be kicked out of Gold Client:

Figure 1.23



# Additional SAP Security Required for Gold Client


Along with the Gold Client Authorization Object (ZGCSGCSGCS), additional authorizations are required for use with Gold Client. These include S\_TCODE, S\_TABU\_DIS and S\_DATASET.

## S\_TCODE

Access to run transaction /HTG/ZGOLD is needed. As of Gold Client version 8.7.4, all /HTG/\* transactions need to be defined in the authorization object to accommodate the CALL TRANSACTION statements present in SAP Code.

S\_TCODE:

Figure 1.24




## S\_TABU\_DIS

All Gold Client tables have been assigned to authorization group HTG and are all within the /HTG/ namespace. This object will allow Security to develop roles that only give table maintenance access to /HTG/ tables without compromising access to non-Gold Client tables. This provides the ability to change and display Gold Client tables.

S\_TABU\_DIS:

Figure 1.25




## S\_DATASET

If a user has authorization to export data within Gold Client, then the S\_DATASET authorization object is required to write to the Gold Client File Path.

**Note:** The following screen capture showing the physical file path of /usr/sap/trans/\* is **only an example**. The actual file path assigned to the customer's Gold Client Security Roles must match the Gold Client Directory that is defined within the customer's system (check in transaction FILE for the object named /HTG/GC). All other details in the below capture can be safely replicated in the Gold Client Security Roles assigned.

S\_DATASET:

Figure 1.26




As of Gold Client 8.7.2025.02, The Setup Confirmation utility has been enhanced to call the Gold Client file directory to check for sizing details. This enhancement requires additional

access to perform the necessary OS-level command. This is strictly optional access which is not required for any other Gold Client functionality.

### ***S\_LOG\_COM (optional)***


---

Authorization to Execute Logical Operating System Commands




### ***S\_C\_FUNCT (optional)***

---



If the user does not have S\_LOG\_COM and S\_C\_FUNCT access, then this message will appear and no sizing details will be displayed



## **RFC Destinations in Gold Client**

---

RFC Destinations are required for the Import Options and Subset Sync functionality within Gold Client. The Import Options functionality allows the users to automatically import data into a Gold Client Target system (if configured), while Subset Sync functionality gives users the ability to export data from a source system that will automatically trigger the same data export from a connected system (if configured to do-so; an example of this would be a data export from ECC that automatically exports data from CRM or SRM). *Please note that RFC users will require additional standard SAP RFC authorization objects in order to work correctly in the SAP environment and are not documented in this guide.*

### ***Import Options - RFC Users***

---

The RFC that is used for the Import Options functionality must be setup (in SM59) as a named user. The import options functionality will not work if the RFC is setup with 'Current User'

selected. An example of this can be seen where the RFC has an actual user assigned and the 'Current User' checkbox is not set (Fig. 1.27)

Figure 1.27

The screenshot shows the 'Logon & Security' tab in SAP. Under the 'Logon Procedure' section, the following fields are visible: Language (EN), Client (200), User (ALARGENT), and PW Status (saved). To the right of the User field is an unchecked checkbox labeled 'Current User'. Below this section, the 'Trust Relationship' is set to 'No' (selected with a radio button), and the 'Logon Screen' checkbox is also unchecked.


The RFC User is defined in the target system (for auto-import functionality) and should have the following SAP object authorizations:

## S\_TCODE

Access to run transaction /HTG/ZGOLD is needed. As of Gold Client version 8.7.4, all /HTG/\* transactions need to be defined in the authorization object to accommodate the CALL TRANSACTION statements present in SAP Code.

S\_TCODE:

Figure 1.28




## S\_TABU\_DIS

All Gold Client tables have been assigned to authorization group HTG and are all within the /HTG/ namespace. This object will allow Security to develop roles that only give table maintenance access to /HTG/ tables without compromising access to non-Gold Client tables. This provides the ability to change and display Gold Client tables.

S\_TABU\_DIS:


Figure 1.29



## S\_DATASET


An auto-import user will be importing data into the target environment and will need access to the Gold Client directory in which Gold Client is assigned to. The following authorizations are needed for the Auto Import RFC user to import data.

**Note:** The following screen capture showing the physical file path of /usr/sap/trans/\* is **only an example**. The actual file path assigned to the customer's Gold Client Security Roles must match the Gold Client Directory that is defined within the customer's system (check in transaction FILE for the object named /HTG/GC). All other details in the below capture can be safely replicated in the Gold Client Security Roles assigned.



## ZGCSGCSGCS

An auto-import user will need authorizations 50 and 54 from the ZGCSGCSGCS authorization object:




## Subset Sync - RFC Users

The Subset Sync functionality uses an RFC Destination to submit the export on a connected system. An existing RFC Destination can be used, or a new one can be created specifically for Gold Client Subset Sync jobs.

RFC Users for Subset Sync should be setup as a communication user on the connected system. If the 'Current User' option is used instead for the RFC, exports in the background will fail. Submitting exports in the foreground would require the user to log in to the connecting system. The User ID will require access to execute Gold Client functions on the connected systems.

An example of an RFC Destination for Subset Sync is below from transaction SM59 (Fig 1.32).




The RFC User is defined in the connected source (export) system and should have the following SAP authorizations:

## S\_TCODE

Access to run transaction /HTG/ZGOLD is needed. As of Gold Client version 8.7.4, all /HTG/\* transactions need to be defined in the authorization object to accommodate the CALL TRANSACTION statements present in SAP Code.

S\_TCODE:

Figure 1.33




## S\_TABU\_DIS

All Gold Client tables have been assigned to authorization group HTG and are all within the /HTG/ namespace. This object will allow Security to develop roles that only give table maintenance access to /HTG/ tables without compromising access to non-Gold Client tables. This provides the ability to change and display Gold Client tables.

S\_TABU\_DIS:


Figure 1.34



## S\_DATASET


An RFC User that is used for Subset Sync functionality will need access to the Gold Client directory which is defined in your SAP environment in order to export the data successfully.

**Note:** The following screen capture showing the physical file path of /usr/sap/trans/\* is **only an example**. The actual file path assigned to the customer's Gold Client Security Roles must match the Gold Client Directory that is defined within the customer's system (check in transaction FILE for the object named /HTG/GC). All other details in the below capture can be safely replicated in the Gold Client Security Roles assigned.



## ZGCSGCSGCS

An RFC user will need the following activities (40,41,42,46) from the Gold Client Authorization Object, ZGCSGCSGCS in order to export data successfully.




## Appendix

The following content provides screen captures of the Gold Client authorization object activities and where they are located within the Gold Client tool. These screen captures are broken down into which areas the activity belongs to.


### *Client Construct*

Client Construct is located on the left-hand side of the main Gold Client Solutions screen and is strictly a Basis activity used to create and/or refresh clients. The authorization for this should strictly be a responsibility of the Basis Team. Activity numbers 01 through 04, plus 65 control these buttons. Each activity is controlled by the authorization object.

01 Client Construct: Client Exporter: Transport Request




02 Client Construct: Client Exporter: Direct Export




01 Client Construct: Client Exporter: Transport Request

02 Client Construct: Client Exporter: Direct Export


*Activities 01 and 02 are both required for the R3Trans Processing Method*




03 Client Construct: Client Importer: Transport Request





04 Client Construct: Client Importer: Direct Input






- 03 Client Construct: Client Importer: Transport Request
- 04 Client Construct: Client Importer: Direct Input

Activities 03 and 04 are both required for the R3Trans Processing Method



- 65 Data Transform: Client Construct




## ***Repository Replicator***


---

Repository Replicator functions Object Alignment and System Build Plus are accessible from the main Gold Client Solutions screen. Object Alignment is used to copy SAP repository objects (programs, function modules, table structures, etc.) between systems, and System Build Plus is used to create a new system "shell" (no customizing and no data).


The authorization for these activities should strictly be a responsibility of the Basis Team. Activity numbers 05 through 09 control these functions. Each activity is controlled by the authorization object.

- 05 Repository Replicator: Object Alignment







06 Repository Replicator: Create Transport of Object Difference




07 Repository Replicator: Recall Previous Run



08 Repository Replicator: Additional Objects



09 Repository Replicator: System Build Plus




## ***Data Echo***

---

Data Echo is located at the top center of the main Gold Client Solutions screen and is used to copy subsets of data between systems. Activity numbers 10 through 56 control the buttons within the Data Echo screens. Each activity is controlled by the authorization object.

## **Data Snap**

10 Data Echo: Data Snap



- 11 Data Echo: Data Snap: Schedule Job  
 Schedule Job
- 12 Data Echo: Data Snap: Show Count  
 Show Count
- 13 Data Echo: Data Snap: Save As Scenario  
 Save As Scenario
- 14 Data Echo: Data Snap: Import Trigger  
 Import Options
- 15 Data Echo: Data Snap: Subset Sync  
 Subset Sync
- 16 Data Echo: Data Snap: Data Transform  
 Data Transform
- 17 Data Echo: Data Snap: Data Type Manager  
**Data Snap**  
 Data Type Manager

## Intelligent Slice

- 20 Data Echo: Intelligent Slice  
 Intelligent Slice

**Intelligent Slice**


Execute

Export ID


Enter Description

## Scenario Segment


- 30 Data Echo: Scenario Segment  
 Scenario Segment



31 Data Echo: Scenario Segment: Scenario Manager



32 Data Echo: Scenario Segment: Data Type Manager






90 Scenario Manager: Manage All Users

Allows users to deselect the 'Show My Scenarios Only' setting within the Scenario Manager function



## Export Control

40 Data Echo: Export Control



41 Data Echo: Export Control: Change Mode

The 'Adjust Date Range' button can be used when granted this activity




42 Data Echo: Export Control: Create Export ID



43 Data Echo: Export Control: Delete Export ID




44 Data Echo: Export Control: Show All Exports



45 Data Echo: Export Control: Execute in Foreground




46 Data Echo: Export Control: Schedule Job




47 Data Echo: Export Control: Import Trigger



48 Data Echo: Export Control: Subset Sync




49 Data Echo: Export Control: Data Transform



## Import Control

50 Data Echo: Import Control



**Import Control**

Refresh

File creation date  to

User who ran Export  to

Export ID  to



Default File Path

Execute in Foreground | Schedule Job | Delete Files | Maintain User Exits


51 Data Echo: Import Control: Details

This authorization activity is no longer relevant as of version 8.4.1

52 Data Echo: Import Control: Report



53 Data Echo: Import Control: Execute in Foreground




54 Data Echo: Import Control: Schedule Job




55 Data Echo: Import Control: Delete Files



56 Data Echo: Import Control: Generate & Activate IM



57 Data Echo: Import Control: Sizing Report: Export File




**Note:** S\_GUI Authorization activities 02 and 61 are also needed

## ***Transformation Rules***

---


Data Transformation is located at the lower middle of the main Gold Client Solutions screen and is used to transform (scramble, mask) data during the export process. Activity numbers 60 through 67 control the buttons within the Data Transform screens. Each activity is controlled by the authorization object.

60 Data Transform: Transformation Setup



Read-Only Access to Transformation Rules

61 Data Transform: Change Rules



62 Data Transform: Maintain Disallowed Fields



63 Data Transform: Maintain List Values



64 Data Transform: Maintain Default Rules




65 Data Transform: Client Construct



Activities 66 and 67 are accessed via the Transformation Audit function



66 Data Transform: Export TRA Details



67 Data Transform: Display Transformed Fields



## ***Transformation Default Rules Security/Use***

---

A default transformation rule can be assigned to one or more datatypes. Once this assignment is made, these default rules will always be used during the export process.

If a user does not have Activity 64 assigned, they do not have access to the Maintain Default Rules button. This button is the only way Default Rules can be assigned. This security model therefore allows a transformation standard to be set for all exports of a specific datatype and prevents Gold Client end-users from circumventing that standard. Data Transformation

buttons within Client Exporter (activity 65), Data Snap (activity 16) and Export Control (activity 49) can also be removed from the users so to not change the rule settings at time of export.

## ***Data Discard***

---

Data Discard is located at the lower center of the main Gold Client Solutions screen and can be used to delete subsets of data in all systems except for Production. Activities 70 through 75 control the buttons within the Data Discard screens. Each activity is controlled by the authorization object.

70 Data Discard: Delete Data

Field	Value	to
File creation date	20.08.2023	
User who ran Export	LFOSTER	
Export ID		
Default File Path	/usr/sap/trans/goldclient/	

71 Data Discard: Details

This authorization activity is no longer relevant as of version 8.4.1

72 Data Discard: Report

- Data Detail Report
- Sizing Report
- Simulate Delete


73 Data Discard: Execute in Foreground

Execute in Foreground

74 Data Discard: Schedule Job

Schedule Job

75 Data Discard: Delete Files



## ***Configuration***


---

Configuration is located on the bottom right of the main Gold Client Solutions screen and can be used to Display or Change the Gold Client Configuration depending on what activities are provided to the users. Activities 80 through 87 and 91 control the buttons within the Configuration menu of Gold Client. Each activity is controlled by the authorization object.

80 Configuration: Display Only




81 Configuration: Administration




***As of GC 8.7, Activity 82 is replaced with Activity 81***

82 Configuration: Installation/Setup




83 Configuration Framework Display Only



84 Configuration Framework Client Construct: Change Access



85 Configuration Framework Data Echo: Change Access



**As of GC 8.7, Activity 86 is replaced with Activity 81**

86 Configuration: Utilities

**As of GC 8.7, Activity 87 replaced with Activity 81**

87 Configuration: Advanced Utilities

**As of GC 8.7, Activity 91 is no longer needed**

91 Configuration: Utilities: HR

## ***Post Process***

---

Activities 88 and 89 are accessible from the main Gold Client Solutions screen via the Post Process function that is located within the Data Echo Group.

88 Configuration: Utilities: Finance

***Post Import Utilities (Optional)***

Utility


- Finance
  - Balance Recalculations
  - Reconcile FI Secondary Indexes

89 Configuration: Utilities: Conversions

- Conversion
  - Configuration
    - Maintain Change Doc Userexit Config
  - Update Change Document Client
  - Utility to Update Client Value
  - Update Person Where-Used Addr Client

Activities 100-130 are assigned for the use of the old Data Wave functionality and for accessing the underlying configuration. Data Wave was redesigned in Gold Client version 8.7.1 and therefore the Security Objects below are no longer applicable to the redesign for Data Wave. The only authorization needed to reach Data Wave and the screens within Data Wave is activity 100. To export data with Data Wave, access will be required for Client Exporter and Export Control functionalities.

100 Data Wave: Cockpit



As of Version 8.7.1, authorization objects 101-130 are no longer required for use with Data Wave and are not required to utilize the functionality in this area of the tool.

## Support Information

---

Qlik Analytics (ISR) Ltd. can be contacted either by telephone or via email. Any support related issue regarding problems with or use of the Gold Client software and process can be reported for resolution.

If our offices are closed, or staff is unable to directly respond to a support request, we will respond within 24 hours of the initial call. Problems related to the export or import processing may require code enhancements. If a code enhancement or fix is required, resolution time may vary.

As per the maintenance agreement, any repairs or enhancements to the Gold Client software will immediately be deployed to all customers up to date with their maintenance contract. It is the choice of the customer as to if and when such enhancements are implemented. In addition, customers may request a planning session with Qlik to review changes in the software and how the changes might impact their environment.

We can also be contacted to discuss application or feasibility of using the Gold Client process to resolve a current challenge the project team faces. When this is required, a planning session can be scheduled in advance to ensure proper participation by both Qlik and the client.

Corporate Offices:

QLIK TECHNOLOGIES INC.  
211 South Gulph Road  
Suite 500  
King of Prussia, PA 19406  
United States

Website:

<https://www.qlik.com/us/products/qlik-gold-client>

Contact:

[goldclient.support@qlik.com](mailto:goldclient.support@qlik.com)

1-877-484-8982 (Toll Free in the USA)