

INSTALLING QLIK INSIGHT BOT NLU



Qlik Insight Bot™

Copyright 2017-2019, QlikTech International AB. All rights reserved.

Contents

- Introduction 2
- Prerequisite..... 2
- Changing the Root Directory of Docker Image Installation 3
- Installing Qlik Insight Bot NLU..... 4
- Upgrading Qlik Insight Bot NLU 6
- Scheduling Docker Restart..... 7
- Appendix I – Converting certificates from pfx to pem format..... 8

Introduction

Qlik Insight Bot NLU is a brain of Qlik Insight Bot. It is responsible to understand what user is asking and looking for. Qlik Insight Bot NLU performs classification and featurization of the queries asked by the user which is needed to form appropriate response by Qlik Insight Bot.

The purpose of this document is to guide you how to install Qlik Insight Bot NLU.

Prerequisite

To install Qlik Insight Bot NLU, you will need below listed items installed/on-hand.

- Latest version of Docker
- Docker Compose Utility
- Docker Compose File
(should be available with Qlik Insight Bot installation package)
- A docker login credential which mentioned in license email to access Qlik Insight Bot NLU private images

Changing the Root Directory of Docker Image Installation (optional)

By default, all docker images are installed at `"/var/lib/docker"` directory. However, if required, you can change the default image installation directory by following below instruction.

1. Change the current directory to `etc/docker`.

```
cd /etc/docker/
```

2. Create and open **daemon.json** file in edit mode.

```
nano daemon.json
```

3. Copy below lines and paste the same in the editor.

```
{
    "graph": "<directory where you want to install images>",
    "storage-driver": "overlay"
}
```

4. Press **ctrl + x** to exit the editor.
5. Press **Y** to save changes.
6. Make sure the file name is **daemon.json**, press **Enter**.
7. Let's make sure that the file is created with required content.

```
cat daemon.json
```

8. The output will be like following

```
root@ubuntu:~# cat daemon.json
{
    "graph": "/data/docker",
    "storage-driver": "overlay"
}
root@ubuntu:~#
```

9. Reload the docker daemon settings.

```
sudo systemctl daemon-reload
```

10. Restart docker.

```
sudo systemctl restart docker
```

11. Make sure that the root directory has been changed successfully.

```
docker info
```

12. Check the path of **Docker Root Dir** in output of previous command.

```
Name:
ID:
Docker Root Dir: /var/lib/docker
Debug Mode (client): false
Debug Mode (server): false
Registry: https://index.docker.io/v1/
Labels:
Experimental: false
Insecure Registries:
127.0.0.0/8
```

Installing Qlik Insight Bot NLU

Qlik Insight Bot NLU is required to be installed on a Linux machine. Follow the below steps to install the NLU on Linux machine.

1. You have been provided with a file named **docker-compose.yml**, copy and paste the same in Linux machine at desired location.
2. Open the yml file in text editor and change the below parameters in the file and save them.

Note: NLU can run with/without HTTPS.

Version	The version of Docker Compose File which is 3.6 by default. Check the compatibility with your Docker engine from here .
isHttps	If set true, the NLU runs on HTTPS else on HTTP.
Certificate path	Provide the physical path of SSL certificate (.pem) before the “:” sign under volumes section if you want to bind your own domain certificate. e.g. <Directory where the certificate is stored>:/nlu/Certificates/ Note: If no certificate provided, the NLU will generate a self-signed certificate automatically.

3. Once you make above changes in yml file, open **Terminal** and change the directory and point it where the yml file has been stored.
4. Login to Docker. Use the username and password provided in the License Email.

```
docker login -u {username} -p {password} qlik-docker-  
insightbot.bintray.io
```

In case you encounter “Access Denied” error at the time of login, use below command and try to login once again.

If you are installing NLU in the **Ubuntu machine**:

```
sudo apt install gnupg2 pass
```

If you are installing NLU in the **CentOS Machine**:

```
sudo yum install gnupg
```

If you are installing NLU in the **RHEL Machine**:

```
sudo yum install gnupg
```

In case you encounter “docker.socket file does not have permission” error, use below commands and try to login once again.

```
sudo chgrp docker /lib/systemd/system/docker.socket  
sudo chmod g+w /lib/systemd/system/docker.socket
```

5. Execute below command to install Qlik Insight Bot NLU.

```
docker-compose up
```

Above command fetches the images from docker repository and execute them. The name of the images is –

1. qlik-docker-insightbot.bintray.io/nlu_db
2. qlik-docker-insightbot.bintray.io/nlu_duckling
3. qlik-docker-insightbot.bintray.io/nlu

If during the installation of Qlik Insight Bot NLU, you see the message “NLU is exited with code 0”, use below commands to restart the process.

```
Ctrl + C
```

```
docker-compose up
```

If the above command fails to fetch the images aforementioned, it is required to pull all the images manually using below command.

```
docker pull <image name>
```

Below command gives you list all of fetched images

```
docker images
```

Execute below command to install Qlik Insight Bot NLU.

```
docker-compose up
```

Qlik Insight Bot NLU should be up and running now.

Upgrading Qlik Insight Bot NLU

1. Before upgrading Qlik Insight Bot NLU it is required to remove the images.

```
docker system prune -a
```

If it is instructed to remove volumes (refer the Release document), use below command to remove volumes.

```
docker volume prune
```

2. Get the updated **docker-compose.yml** file and replace it with the exist one, execute below command to install Qlik Insight Bot NLU.

```
docker-compose up
```

Scheduling Docker Restart

You can also set a schedule to restart docker. The reason of restarting docker is to release unused memory. On each restart, Docker automatically load the latest available model.

Use below set of command to schedule the restart.

1. Edit a Crontab file. The crontab is a list of commands that you want to run on a regular schedule, and also the name of the command used to manage that list.

```
crontab -e
```

2. Schedule the time to restart docker.

```
59 23 * * 1-7 docker restart <NLU container name>
```

Min Hr Days-in-week

By default, the <NLU container name> will be **qib_nlu**.

3. Press **Ctrl + X** to exit from edit mode of Crontab file, press **Y** to save the changes made in file.
4. To see the list of Cron jobs.

```
crontab -l
```


Appendix I – Converting certificates from pfx to pem format

In order to convert **pfx** file to **pem** file you need to follow below instruction and for that you are going to need **open SSL** which you can download it from [here](#).

1. Open Bin where openssl.exe is installed. Copy and Paste **pfx** and **key** files of SSL certificate of server on which you are going to install Qlik Insight Bot NLU to this directory.
2. Run **openssl.exe** as an administrator.
3. Execute below commands one after another.

```
openssl pkcs12 -in <your_file.pfx> -nocerts -out NluEnc.key
```

- Enter the certificate password and hit enter. If no password had been set for the certificate, hit enter.
- Set the pass phase. Its length must be no shorter than 4.

```
openssl rsa -in NluEnc.key -out nlu_key.pem
```

- Enter the pass phase (set earlier)

```
openssl pkcs12 -in <your_file.pfx> -clcerts -nokeys -out nlu_cert.pem
```

- Enter the certificate password one more time.

These commands will generate –

nlu_key.pem and **nlu_cert.pem** which will be required during Qlik Insight Bot NLU installation.

--- EOD ---